

IMARK

PRODUCT DESCRIPTION



14RUEC EQUIPMENT CABINET

14RU Fully Enclosed Equipment Cabinet

Imark Stock # [708021](#)

Features:

- 14RU size
- Removable Lockable Front Door
- Concealed Hinges and double Locks
- Removable Rear Panel
- Recessed Removable Rear Cable Entry Panel
- Handles to aid transport and manoeuvrability
- Phosphated electrostatic powder coated metal Cabinet
- Adjustable Glides for levelling
- Sealed Cabinet
- Earth Bolt and 150mm Extension Feet included

DESCRIPTION:

The IMARK 14RUEC Equipment Cabinet is a compact equipment Cabinet that has been specifically designed for use at/with radio sites. It features all metal construction, is phosphate treated and powder coated for long life, and is foam sealed to prevent the ingress of dust, moisture, and insects or vermin. The front door includes two locks, has concealed hinges for security. The removable rear panel is also foam sealed. Four handles are fitted to the top of the cabinet to aid handling and manoeuvrability.

The IMARK 14RUEC Equipment Cabinet also includes a recess at the rear of the cabinet as the cable entry point to allow location of the cabinet close to walls. A removable cable entry panel is standard and is ideal for mounting cable connectors without compromising the sealed integrity of the cabinet.

19" equipment rails are provided at the rear as well as at the front thus permitting rear mounting of equipment if required. A 6mm brass Earth Bolt is also provided to permit proper earthing of the equipment cabinet.

An optional (at extra cost) Solar cable entry panel is available. This Solar cable entry panel includes pre-cut holes to accept connectors for one AC Input, one Battery connector, one Solar Panel connector, two RF Cable bulkhead connectors, and one DB25 connector. Space is also available on this panel to mount an AC Transient Barrier. Equipment Slides are also available as an option at extra cost.

SPECIFICATIONS:	
Construction	Mild Steel
Finish	Iron phosphate pre-treatment with electrostatic powder coating
Front Door Aperture Size	510(W) x 680(H) mm
Rear Cover Aperture Size	510(W) x 485(H) mm
Unit Dimensions	580 (W) x 600 (D) x 758(H) mm (excluding protrusions)
Shipping Dimensions	720 (W) x 700 (D) x 880 (H) mm
Unit Weight	23 Kg's
Shipping Weight	36 Kg's
Inclusions	Feet Extensions x 4, Keys x 2, Feet x 4.
Rating	IP54
Imark Stock #	708021
Options	Equipment Slides, Solar Cable Entry Panel